



Specification:

ECO-Jack heavy duty hydraulic jacks are available in five different series with payloads up to 25 tons. The adjustability of the lifting claw on all ECO-Jack is patented easy: Lift the claw with just one hand, take it horizontally out of the groove plate and insert it in a new position - done. Easy to use with a low risk of injury. The integrated pump requires no additional equipment. From the EJ100-3S, external manual or electric pumps can also be connected. For all areas of application in which the standard range is insufficient, we design special solutions that are individually tailored to the customer needs.

Technical data of hydraulic jacks:

#	01 250 31 10	520 bar	1000 ml	72 kg
1/	NH = 0,4 mm / stroke SH = 1,0 mm / stroke	HH = 140 mm	25000 kg	20000 kg
	L x B x H 388 x 392 x 330 mm	#V 3 x 100 mm	A _{min} = 30 mm	LH LH = 60 mm

Please always observe the operating instructions, their safety instructions and local conditions!

#	Part No.	Maximum operating pressure in bar	Oil quantity in the tank / cylinder in ml. Standard oil HLP 32 other oils on request	Weight kg
	Maximum stroke in mm	Maximum lifting load with the lifting head in kg	Maximum lifting load with lifting claw in kg	Dimensions in mm L x B x H
A	Insertion height in mm	LH Useable length of lifting claw in mm		#V Adjustment positions Distances in mm